



# XMG-62

## Compact Analog Mixer

### Features

- 2 MIC Input Channels
- 2 Stereo Input channels
- 3-band EQ
- 1 AUX Send
- 2-Track Input


XMG-62 is the most compact mixer of the XMG range. It offers a total of 6 inputs including 2 mono and 2 stereo channels. It is the Swiss Army Knife of the mixers for users who need to mix few sound sources with professional quality, functionality and simplicity.

The XMG-62 has been designed with the same quality standard as higher models. It is equipped with ultra-low noise discrete Mic Preamps with +48V Phantom Power and it uses low distortion electronic circuitry. Inputs and outputs feature XLR, 1/4" jacks and RCA connectors for higher flexibility.



Mono Inputs		Main Mix Section	
Microphone Input	Electronically balanced, XLR-F	Max. output	+22dBu un-balanced 1/4" jacks
Frequency Response:	10Hz to 55kHz, $\pm 3$ dB	AUX adjust range	Off to +10dB
Distortion (THD & N)	< 0.01% at +0dB, 22Hz ~ 22kHz	Hum & Noise	< -90dB @20Hz ~ 22kHz, 1 channel & main level:0dB, the other: minimum
Gain range	-10dB to -60dB	Channel Crosstalk	< -80dB @0dB 20Hz ~ 22kHz, main level:0dB, the other: minimum
Phantom power	+48V with switch control	<b>USB Interface (Option)</b>	
<b>Stereo Input</b>		Version	Fully compliant with USB1.1
Line Input	Electronically Balanced	Sampling rate	8kHz, 16kHz, 32kHz, 11.023kHz, 22.05kHz, 44.1kHz, 48kHz
Gain range :	-10dB to -50dB	Dimension (W x D x H)	300 x 255 x 60mm (11.8" x 10.04" x 2.4")
Max. input	+22dB		
SNR	>90dB		
Impedances	line input: Electronically balanced JACK		
Sensitivity range	+20dB to -20dB		
Microphone input	1.5k $\Omega$		
All Other Inputs	10k $\Omega$ or greater / Tape out:1k $\Omega$		
All other outputs	120 Ohms		

Specifications subject to modification without notice



## SEIKAKU TECHNICAL GROUP LIMITED

NO.1 LANE 17, SEC.2, HAN SHI WEST ROAD, TAICHUNG 40151 TAIWAN

Tel: +886-4-22313737 Fax: +886-4-22346757 www.seikaku.hk