



PA-20M / PA-20HM

Class-D Amplifier



Features

- 20 W, Class-D
- 4 Ω (PA-20M)
- 4 Ω, 70V/100V (PA-20HM)
- 2 Mic/Line IN, 1 stereo Aux IN
- MP3 Player - Siren
- 12~15 V DC supply

The PA-20M and PA-20HM are very compact amplifiers specifically designed for fixed or mobile applications. Their small size and light weight make easy their integration in little space. The 12V DC operation perfectly fits for portable use or for installations where direct AC power supply is not available. They are an ideal solution for zoning, information points, ticketing counters and vehicles using rooftop speaker system. Both amplifiers feature a MP3 player with a UBS port, plus a siren triggered with a push button from the front panel. 2 Mic inputs are available with TRS 6.35mm jacks, plus 1 Aux stereo input on the rear panel with RCA connectors. All volume controls are on the front panel and it includes a simple EQ setting. The output section uses euro block connectors and features 4Ω load for PA-20M and 4Ω, 70/100 V load for PA-20HM.

Specifications

Power Supply	DC 12~15V, 2A
Rated Output Power	20W
Max Rated Power Consumption	30W
Rated Output	4Ω
S/N Ratio	> 65dBu
THD	1%, -37dBu ± 2dB (MIC1~MIC2)
Input Sensitivity (1 kHz)	-11dBu ± 2dB (AUX)
Noise or Hum	25mV
MP3	USB
Output	4Ω (PA-20M) 4Ω, 70V/100V (PA-20HM)
Dimension (W x D x H)	161 x 101 x 45 mm
Weight	PA-20M: 0.89 kg, PA-20HM: 0.96 kg

Specifications subject to modification without notice

Under-table/wall mounting plate



PA-20HM

PA-20M



SEIKAKU TECHNICAL GROUP LIMITED

NO.1 LANE 17, SEC.2, HAN SHI WEST ROAD, TAICHUNG 40151 TAIWAN

Tel: +886-4-22313737 Fax: +886-4-22346757 www.seikaku.hk