



CSB-10T / CSB-30T

Surface Mount Speakers

Features

- 10W - 30W
- 3" - 4" full range transducer
- 70V, 100V

CSB-10T and CSB-30T are design and compact surface mount speakers to broadcast speech and music. The speakers are equipped respectively with a 3" and 4" full range transducers. With 10W and 30W power, both models offer optimal performances for any kind of application. They integrate high impedance outputs for 100V and 70V installations. The built-in transformer gives the choice of three or four power levels depending on the model. Made of ABS resin the cabinet is scratch and shock resistant.



Specifications

MODEL	CSB-10T	CSB-30T
Speaker Type	Passive with transformer	Passive with transformer
Transducer	1 x 3" full range speaker	1 x 4" full range speaker
SPL (1W/1m)	85dB (+/-3dB)	90dB (+/-3dB)
Power Rating	70V: 1.25, 2.5, 5, 10W 100V: 2.5, 5, 10W	70V: 3.75, 7.5, 15, 30W 100V: 7.5, 15, 30W
Frequency Response	160Hz ~ 20kHz	76Hz ~ 18kHz
Rated Impedance	70V: 4kΩ, 2kΩ, 1kΩ, 500Ω 100V: 4kΩ, 2kΩ, 1kΩ	70V: 1.3kΩ, 665Ω, 333Ω, 163Ω 100V: 1.3kΩ, 665Ω, 333Ω
Connector	Wiring terminal	Wiring terminal
External Controls	Power selecting switch	Power selecting switch
Power Supply	N/A	N/A
Color	Black / White	Black / White
Dimensions (W x D x H)	115 x 107 x 175 mm (4.5" x 4.2" x 6.9")	136 x 140 x 206 mm (5.35" x 5.51" x 8.11")
Weight	0.9kg (2 lbs.)	2.2-2.4 kg (4.85-5.3 lbs.)

Specifications subject to modification without notice



SEIKAKU TECHNICAL GROUP LIMITED

NO.1 LANE 17, SEC.2, HAN SHI WEST ROAD, TAICHUNG 40151 TAIWAN

Tel: +886-4-22313737 Fax: +886-4-22346757 www.seikaku.hk